



P8H67-V

REV 3.0 - Neue H67 B3 Revision - Intel® H67-Plattform - GPU-Übertaktung dank ASUS GPU Boost-Technologie

- ASUS GPU Boost - Prozessorleistung sofort steigern
- Protect 3.0-Technologie - effektiver Schutz für Umwelt und System
- EFI BIOS (EZ Modus) - Flexible und einfache BIOS-Benutzeroberfläche
- AI Suite II - Direkter Zugriff auf innovative ASUS-Features
- Extrem schnelle Datenübertragungsraten mit USB 3.0- & SATA 6Gb/s-Unterstützung
- MemOK! - Speicherprobleme gehören der Vergangenheit an

[Alle Infos zur neuen B3 Revision...](#)



Spezifikationen

Spezifikationen

CPU	Intel® Socket 1155 for Intel® 2 nd Generation Core™ i7 Processor/Core™ i5 Processor/Core™ i3 Processor/ Support Intel® 32nm CPU Supports Intel® Turbo Boost Technology 2.0 * The Intel® Turbo Boost Technology 2.0 support depends on the CPU types. * Refer to www.asus.com for Intel® CPU support list.
Chipset	Intel® H67(B3) Chipset
Memory	4 x DIMM, Max. 32 GB, DDR3 1333/1066 Non-ECC, Un-buffered Memory Dual Channel memory architecture Supports Intel® Extreme Memory Profile (XMP) * According to Intel® SPEC, the Max. 32GB memory capacity can be supported with DIMMs of 8GB (or above). ASUS will update QVL once the DIMMs are available on the market. * Please refer to www.asus.com or user manual for Memory QVL. * When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.
Expansion Slots	1 x PCIe 2.0 x16 [blue] (single at x16 mode) 1 x PCIe 2.0 x16 *[black] (at x4 mode, compatible with PCIe x1 and x4 devices) 2 x PCIe 2.0 x1 3 x PCI * PCIe x1 slot shares the bandwidth with PCIe x16_2 slot. ** Due to CrossFireX™ limitation, DO NOT use the PCIe x1 slot when you install two CrossFireX™ graphics cards on both the PCIe x16 slots to set up a CrossFireX™ configuration. *** To disable the PCIe X1 slot, refer to the Onboard Devices Configuration section in the BIOS for details.
VGA	Multi-VGA output support: HDMI, DVI-D, RGB - Supports RGB with max. resolution 2048 x 1536 @ 75Hz - Supports DVI with max. resolution up to 1920 X1200 @ 60 HZ - Supports HDMI with max. resolution up to 1920 X1200 @ 60 HZ Maximum shared memory of 1748 MB
Multi-GPU Support	Supports ATI® Quad-GPU CrossFireX™ Technology
Storage	Intel® H67(B3) Express Chipset 4 xSATA 3.0 Gb/s ports (blue) 2 xSATA 6.0 Gb/s ports (gray) Intel Rapid Storage Technology Support RAID 0,1,5,10 VIA VT6415 PATA controller 1 xUltraDMA 133/100 for up to 2 PATA devices
LAN	PCIE Gigabit LAN
Audio	ALC887 8-Channel High Definition Audio CODEC
USB	ASMedia® USB 3.0 controller - 2 x USB 3.0/2.0 ports (blue) at back panel

Intel® H67(B3) Express Chipset
- 12 x USB 2.0/1.1 ports (8 ports at mid-board, 4 ports at back panel)

ASUS Unique Features	<ul style="list-style-type: none">- Turbo V- Auto Tuning- Anti-Surge Protection- GPU Boost- Mem OK!- ASUS Fan Xpert- AI Suite II- EPU- CrashFree BIOS 3- EZ Flash 2- MyLogo 2
Back Panel I/O Ports	<ul style="list-style-type: none">1 x PS/2 Keyboard/Mouse Combo port1 x DVI1 x VGA1 x HDMI1 x LAN(RJ45) port(s)2 x USB 3.0/2.04 x USB 2.0/1.11 x S/PDIF Out (Optical)8 -Channel Audio I/O
Internal I/O Connectors	<ul style="list-style-type: none">4 x USB connectors support additional 8 USB ports1 x MemOK! switch1 x GPU Boost switch1 x IDE connector2 x SATA 6.0Gb/s connectors4 x SATA 3.0Gb/s connectors1 x CPU Fan connector(s)2 x Chassis Fan connector(s)1 x Power Fan connector(s)1 x S/PDIF Out connector1 x 24-pin ATX Power connector1 x 8-pin EATX 12V Power connector1 x Front panel audio connector1 x COM connector1 x System Panel connector
BIOS	32 Mb Flash ROM , EFI BIOS, PnP, DMI v2.0, WfM2.0,SMBIOS v2.6, ACPI v2 0a, Multi-language BIOS
Accessories	<ul style="list-style-type: none">User's manual1 x UltraDMA 133/100/66 cable2 x SATA 6.0Gb/s cablesI/O Shield
Support Disc	<ul style="list-style-type: none">DriversAnti-virus software (OEM version)ASUS UpdateASUS Utilities
Form Factor	ATX Form Factor 12 inch x 9 inch (30.5 cm x 22.9 cm)
