



BC-12B1LT

Enter a New Visuals

ASUS BC-12B1LT is a p
reading from 12X BD for
strategy, it assures the b
entertainment, creating a



Spezifikationen

Spezifikationen

Farbe	Black
Lesegeschwindigkeit	BD-R : 8X BD-RE : 8X BD-ROM : 12X BD-R(DL) : 6X BD-RE(DL) : 6X BD-ROM(DL) : 6X DVD+R : 16X DVD-R : 16X DVD+RW : 12X DVD-RW : 12X DVD-ROM : 16X DVD+R(DL) : 8X DVD-R(DL) : 8X DVD-ROM(DL) : 12X DVD-RAM : 12X CD-R : 48X CD-ROM : 48X

	BDMV Playback : 2X DVD Video Playback : 4X VCD Playback : 10X
Schreibgeschwindigkeit	DVD+R : 16X DVD-R : 16X DVD+RW : 8X DVD-RW : 6X DVD-R (DL) : 8X DVD-RAM : 12X/48X CD-R : CD-RW : 24X
Writing Mode	DVD+R & DVD+R (DL) : Sequential Write DVD-R & DVD-R(DL) : DAO/Incremental Recording DVD+RW : Random Write DVD-RW : DAO/Restricted Overwrite/Incremental Recording DVD-RAM : Random Write CD-R/RW : DAO/TAO/SAO/Packet Write
Access time	BD : 250 ms DVD : 160 ms CD : 160 ms
Schnittstellen	SATA
Pufferspeicher	2 MB
Betriebssysteme	Windows 7 Windows 2000 Windows XP
Systemanforderungen	Processor: Pentium® D 945(3.4GHz) or higher Memory:1GB or more is recommended HDD:10GB or more Graphics Card: NVIDIA® GeForce 7600 GT or ATI X1600 series or above Use HDCP Compatible display and VGA card to High Definition digital outp To find out more about 3D playback information, visit www.cyberlink.com .
Software	Cyberlink Power2Go Cyberlink PowerDVD with Magic Cinema Cyberlink PowerBackup Cyberlink InstantBurn E-green E-Hammer
Disc Formats	Audio CD, Video CD, CD-I, Photo CD, CD-Text, CD-ROM/XA, Multi-session C
Disc Diameters	12cm/8cm
Mounting Orientation	Vertical and Horizontal (+5° ~ - 5°)
Maße	146 x 170 x 41 cm (WxDxH)
Gewicht	800 g
Stromversorgung	DC+5V ±5%, DC+12V ±10 %
Temperature	Operating : 5 °C to 45 °C Storage : -20 °C to 60 °C

Humidity

Operating : 20 % ~ 80 % (Non-condensing)

Storage : 15 % ~ 90 % (Non-condensing)

lightScribe

Support
