

P5QPL-AM

Specifications

CPU	Intel® Socket 775 Core™2 Quad/Core™2 Extreme/Core™2 Duo/Pentium® dual-core/Celeron® dual-core /Celeron® Processors Compatible with Intel® 05B/05A/06 processors Support Intel® 45nm Multi-Core CPU *Refer to www.asus.com for Intel CPU support list
Chipset	Intel® G41 /ICH7
Front Side Bus	1333/1066/800 MHz 2 x240-pin DIMM, Max. 8 GB, DDR2 1066(O.C.)/800/667 Non-ECC, Un-buffered Memory Dual Channel memory architecture
Memory	** Refer to www.asus.com or user manual for Memory QVL (Qualify Vendor List) *** When installing total memory of 4GB capacity or more, Windows® 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.
Expansion Slots	1 x PCIe x16 1 x PCIe x1 2 x PCI Support PCIe 1.1 Architecture
VGA	Integrated Intel Graphics Media Accelerator (Intel® GMA X4500) - Supports Microsoft® DirectX 10, OpenGL 2.1 - Supports RGB with max. resolution 2048 x 1536@75Hz
Storage	Southbridge 1 xUltraDMA 100 4 xSATA 3 Gb/s ports
LAN	PCIe Gb LAN
Audio	High Definition Audio 6 -Channel CODEC Supports Jack-detect and Multi-Streaming teconologies Supports S/PDIF out interface
USB	8 USB 2.0 ports (4 ports at mid-board, 4 ports at back panel)
Overclocking Features	SFS (Stepless Frequency Selection) - FSB tuning from 200MHz to 800MHz at 1MHz increment Overclocking Protection - ASUS C.P.R.(CPU Parameter Recall)
Special Features	ASUS MyLogo 2 ASUS EZ Flash 2 ASUS CrashFree BIOS 3 ASUS Q-Fan Turbo Key AI NET2
Back Panel I/O Ports	1 x D-Sub 1 x Parallel 1 x PS/2 Keyboard 1 x PS/2 Mouse 1 x LAN(RJ45) port 4 x USB 2.0/1.1

	1 x COM port
	6 -Channel Audio I/O
	2 x USB connectors support additional 4 USB 2.0 ports
	1 x IDE connector
	4 x SATA connectors
	1 x High Definition front panel audio connector
Internal I/O	1 x S/PDIF Out connector
Connectors	System Panel
	1 x Internal Speaker connector
	1 x CD audio-in connector
	24-pin EATX power connector
	4-pin ATX 12V Power connector
BIOS	8 Mb Flash ROM
	AMI BIOS, PnP, DMI2.0, WfM2.0, ACPI2.0, SMBIOS 2.5
	User's manual
	1 x I/O Shield
Accessories	1 x UltraDMA 133/100/66 cable
	1 x SATA cable
	* Note: The floppy disk drive cable is purchased separately
	Drivers
Support Disc	ASUS PC Probe II
	Anti-virus software (OEM version)
	ASUS LiveUpdate Utility
Form Factor	uATX Form Factor
	9.6 inch x 7.6 inch (24.4 cm x 19.3 cm)

The product (electrical , electronic equipment, Mercury-containing button cell battery) should not be placed in municipal waste. Check local regulations for disposal of electronic products.

- All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.
- PCB color and bundled software versions are subject to change without notice.
- Brand and product names mentioned are trademarks of their respective companies.