

MASTER VIEW™ PRO

DUO ACCESS KVM SWITCH



2x8



Features

- * 2 Consoles Control 8 Computers.
- * Cascadable One Level Down To a CS-138A, CS-9138, CS-128A, CS-124A To Control Up To 64 Computers.
- * Supports Audio Functions(Mic. & Speaker).
- * Two Level Password for Security: One Administrator and Four User Passwords.
- * OSD(On Screen Display) Window Automatically Adjusts to Resolution Changes.
- * OSD Channel List Automatically Expands When Cascaded.
- * Supports Microsoft(DOS, Microsoft(Windows 9x / 98SE / ME / NT / 2000, Linux, Netware, FreeBSD, IBM RS6000.
- * Supports DDC2(Display Data Channel 2), 1920 X 1440 Resolution.
- * Special Easy-Stacking Design.
- * Rack Mountable 19"(1U) System Rack.

Specifications

Function		Specification
Computer Connections	Direct	8
	Max	64 (via Daisy Chain)
Port Selection		OSD (On Screen Display)
LEDs	Power	1 (Blue)
	On Line	8 (Orange)
	Selected	8 (Green)
Console Connectors	Keyboard	2 x 6 pin mini-DIN female
	Mouse	2 x 6 pin mini-DIN female
	Video	2 x HDB-15 female
	Audio	2 x Microphone Jacks 2 x Speaker Jacks
Computer Port Connectors		8 x 25 pin D Type female
On Screen Display (OSD)		PC Names; ID Numbers; Port Status
Scan Interval (OSD Select)		User Specified: 1 - 255 secs.
Emulation	Keyboard	PS/2 and PC/AT
	Mouse	PS/2 and Serial
	Video	1920 x 1440; DDC2
Power Consumption		DC 9V; 7.2W (max.)
Operating Temperature		5 - 40° C
Storage Temperature		-20 - 60° C
Humidity		0 - 80% RH
Housing		Metal
Weight		2700 g
Dimensions (L x W x H)		433.5 x 153 x 44 mm (19" 1U)

ATEN INTERNATIONAL CO., LTD.

TEL:886-2-8692-6789 FAX:886-2-8692-6767

CS-228